

XRV750 Africa Twin

Colouring Concept

As Honda's towering 'Adventure Sports' trailblazer, the big Africa Twin looks ready to tackle the desolate wastes of far-off continents like the rugged race machines that annually challenge the world's most demanding international rallies. Its big and rugged V-twin engine delivers an exciting surge of low-end power and torque that drives it through towns and over steep mountains with equal ease. And its impressively styled fairing design complements a quickhandling, long-travel suspension to lend a modern and sporty feel while offering superb wind protection for long-term riding comfort.

For 2001, the globe-trotting Africa Twin takes off for regions unknown in two attractive colour variations that further catch the eye with their exciting graphics and stripes. First up is an impressive tricolor that contrasts dark metallic blue and bright red with dazzling white to leave no question about the Africa Twin's spirit of adventure. Next is a dark and lustrous blackon-black combination that dramatically accentuates the Africa Twin's urban sophistication in its journeys through the cities and backroads of the continent and beyond.

Colours

- Sparkling Red (with Sahara Blue Metallic and Ross White)
- Black







XRV750 Africa Twin

Specifications

Specifications XRV750 Africa Twin (ED-type) (95/1/EC-values)

Engine Liquid-cooled 4-stroke SOHC 52° V-twin

Bore \times Stroke $81 \times 72 mm$ Displacement $742 cm^3$ Compression Ratio9:1

Carburettors 36mm flat-slide CV-type \times 2

Max. Power Output $44kW/7,500min^{-1}$ Max. Torque $62Nm/6,000min^{-1}$

Ignition Digital transistorised with electronic advance

Starter Electric Transmission 5-speed

Final Drive 'O'-ring sealed chain Dimensions (L×W×H) $2,315 \times 905 \times 1,430$ mm

Wheelbase 1,565mm
Seat Height 860mm
Ground Clearance 215mm
Fuel Capacity 23 litres

Wheels Front/Rear Aluminium rim/steel spokes
Tyres Front 90/90–21 54H (Bias-ply)

Rear 140/80 R17 69H (Radial)

Suspension Front 43mm leading-axle fork, 220mm axle travel

Rear Pro-Link with aluminium swingarm,

214mm axle travel

Brakes Front 276mm dual hydraulic disc with dual-piston callipers and sintered metal pads

Rear $\,$ 256mm hydraulic disc with single-piston calliper and resin mould pads

Dry Weight 205kg

All specifications are provisional and subject to change without notice.

